



TS-03
Tangent Section
SR 26 EB - Broad Street - 12+25 to 15+00
SR 26 WB - Commerce Street - 102+00 to 103+00

- REQUIRED PAVEMENT STRUCTURE**
- Ⓐ RECYCLED ASPH CONC 12.5 MM SUPERPAVE, GP 1 OR 2, INCL BITUM MATL & H LIME, 165 LB/YD
 - Ⓑ RECYCLED ASPH CONC 19 MM SUPERPAVE, GP 1 OR 2, INCL BITUM MATL & H LIME, 220 LB/YD
 - Ⓒ RECYCLED ASPH CONC 25 MM SUPERPAVE, GP 1 OR 2, INCL BITUM MATL & H LIME, 550 LB/YD
 - Ⓓ GRADED AGGREGATE BASE CRS, INCL MATL, 12 IN DEPTH
 - Ⓔ MILL ASPH CONC PVMT, 1½ IN DEPTH
 - Ⓕ CONC CURB & GUTTER, 6 IN X 30 IN, TP 7
 - Ⓖ SAFETY EDGE (SEE CONSTRUCTION DETAIL P-7)

GEORGIA
DEPARTMENT
OF
TRANSPORTATION

NOT TO SCALE

REVISION DATES		

STATE OF GEORGIA
DEPARTMENT OF TRANSPORTATION
OFFICE: ROADWAY DESIGN
TYPICAL SECTIONS
SR 26 @ OCMULGEE RIVER

DRAWING No.
5-002